



## Conveyor

The conveyor consists of standard parts, which are advanced and simple in structure, easy to maintain. Our vibrating equipment is adaptable for stationary and mobile crushing plants. They are widely used in mining, metallurgical and coal industry to transfer sandy or lump material, or packaged material. According to different transferring equipment, the transfer system can be one independently or multiconveyers or combined with other transfer equipments. The belt conveyor can be installed horizontally or aslope to meet the needs of different transfer lines. The belt conveyers produced by SJLC can be operated in the circumstance temperature range from 20 centigrade to +40 centigrade. The temperature of transferred material by this belt conveyor should be lower than 50 centigrade.



### Feature Of Conveyor:

Belt Width (mm)	Belt Length /Power (kw)			Belt Speed (m/s)	Capacity (t/h)
400	<12 1.5	12-20 2.2-4	20-25 3.5-7.5	1.3-1.6	40-80
500	<12 3	12-20 4-5.5	20-30 5.5-7.5	1.3-1.6	40-80
650	<12 4	12-20 5.5	20-30 7.5-11	1.3-1.6	131-323
800	<6 4	6-15 5.5	15-30 7.5-15	1.3-1.6	278-546
1000	<10 5.5	10-20 7.5-11	20-40 11-12	1.3-2.0	435-853
1200	<10 7.5	10-20 11	20-40 15-30	1.3-2.0	655-1284