



JS mixer

The series of mixer belongs to double-shaft compulsion concrete mixer and can mix dry-hard, fluid concrete and mortar. Because the tumbling box is enchased high-manganese wearable steel plate and mix vane, have the feature of ruggedization and change expediently. When assembled with feeder, the mixer can be applied as a complete mixing plant of durability, widely used for building, and widely be applied to all type of building site, roadway, bridge, airport, tunnel, etc. The bears the advantage of reasonable designing, operation convenience, reliable work, high efficiency, low lost, low noise and durable service life.



Feature Of JS mixer:

Output capacity		500L	750L	1000L	1500L	2000L
Feed capacity		800L	1200L	1600L	2400L	3200L
Capacity		>25m ³ /h	>37.5m ³ /h	>50m ³ /h	>75m ³ /h	>100m ³ /h
Max. feed lump size(screed/gravel)		80/60mm	80/60mm	80/60mm	80/60mm	80/60mm
Mix vane	Shaft speed	35r/min	31r/min	25.5r/min	25.5r/min	23r/min
	Amount	2*7	2*7	2*8	2*10	2*10
Mix engine	Type	Y180M-4	Y200L-4	T225S-4	Y225M-4	Y280S-4
	Power	18.5KW	30KW	37KW	45KW	75KW
Engine	Type	YEZ132S-4-B5	YEZ132M-4-B5	YEZ160S-4	YEZ180L-4	YEZ180L-4
	Power	5.5KW	7.5KW	11KW	18.5KW	22KW
Water pump engine	Type	50DWB20-8A	65DWB35-5	KQW65-100L	KQW65-100L	CK65-20L
	Power	750W	1.1KW	3KW	3KW	4KW
Elevate speed		18m/min	18m/min	21.9m/min	23m/min	26.8m/min
Overall dimension	Transport state	3050*2300*2680mm	3650*2600*2890mm	4640*2250*2250mm	5080*2250*2440mm	5860*2250*2735mm
	Work state	4461*3050*5225mm	4951*3650*6225mm	8765*3436*9540mm	9645*3436*9700mm	10720*3870*10726mm
weight		4000kg	5500kg	8700kg	11130kg	15000kg
height		1500mm	1600mm	2700 & 3800mm	3800mm	3800mm