



### R pendulum grinder

The machine are mainly used in grinding more than 280 noninflammable and nonexplosive materials with a Moh's hardness below 7 scale, a humidity below 6%, such as barite, calcite, potash, pencil stone, marble, limestone, ceramic, glass and other materials which used in mining, construction, chemical and metallurgy. The size of powder can be controlled ranging from 80 to 325 meshes.



### Feature Of R pendulum grinder:

Models	Roller quantity	Roller size (mm)	Height and diameter of ring (mm)	Max. Feed size (mm)	Product size (mm)	Capacity (t/h)	Power (kw)	Weight (t)	Overall dimension (mm)
3R1410	3	140*100	495*100	8	0.125-0.044	0.2-1.2	7.5	1.6	3340*2200*3200
3R2115	3	210*150	630*150	15	0.125-0.044	0.4-1.6	15	3.6	4500*2800*5800
3R2615	3	260*150	780*150	20	0.125-0.044	0.8-2.5	18.5	4.2	5650*3305*5950
3R2715	3	270*150	830*150	20	0.125-0.044	0.9-2.8	22	4.8	5600*3400*5900
4R3016	4	300*160	880*160	20	0.125-0.044	1.2-3.5	30	8.5	6500*4100*5200
4R3216	4	320*160	970*160	25	0.125-0.044	1.8-4.5	37	15	9900*5800*10580
5R4119	5	410*190	1270*190	30	0.125-0.044	2.5-8.5	75	24.5	10500*6500*13530